

EMOTION

COLORED BODY PORCELAIN TILE

SIZE 8"x40"

RELAX BEIGE



Available size



8"x40"
± 0.35" / 9 mm

Color shading



HAPPY WALNUT



Available size



8"x40"
± 0.35" / 9 mm

Color shading



The colour of tiles printed in this catalogue may differ from actual tiles. Tile color reproductions in this catalogue are representative only. Slight tone and shade variations are inherent in porcelain tiles. Before selecting a colour, we recommend that you contact your local representative, who will provide you with a sample piece of the requested tile.

SIZE 8"x40"

SWEET GREY



Available size



8"x40"
± 0.35" / 9 mm

Color shading



SOFT DARK



Available size



8"x40"
± 0.35" / 9 mm

Color shading



This porcelain tile product is manufactured with a V2 shade variation. Remember that the amount of colour as well as the texture of each piece may vary from tile to tile. Inspect the product immediately upon delivery and select tiles from many boxes during installation to minimize and blend any possible colour difference.

Color Shading




EMOTION

COLORED BODY PORCELAIN TILE

TRIM TILES

INFORMATION

	COVE BASE  6"x12"
RELAX BEIGE	•
HAPPY WALNUT	•
SWEET GREY	•
SOFT DARK	•

RECOMMENDED USE

Emotion is recommended for indoor floors, walls, countertops, and outdoor walls in commercial and residential application. The use of Emotion is not recommended for outdoor application or horizontal exterior surfaces. Landmark recommends an offset no greater than 30%. If a staggered pattern is required for tiles of 20" inches or longer.

CARE AND MAINTENANCE

Do not apply any wax or sealer to the product after installation. Regular cleaning is the best way to keep Emotion tiles looking good. Use clean, hot water (add household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. Please visit lcusa.com. For further information regarding the care and maintenance of Landmark products.

WARRANTY

Landmark guarantees that its products will meet or exceed the performance specifications set out in ANSI A137.1- 2012 and in the performance specifications section of the Landmark general catalogue. For more information, please visit our website at lcusa.com.

