













PORCELAIN VENEER

PHYSICAL PROPERTIES	TEST ASTM	STANDARD A137.1*	RESULTS
 Water absorption *	C373	≤ 0.5%	COMPLY WITH ANSI A137.1
 DCOF Average dynamic coefficient of friction **	ANSI A.326.3	As reported	NOT APPLICABLE
 Skid Resistance	DIN 51097	NOT APPLICABLE	NOT APPLICABLE
	DIN 51130		
 Resistance to freeze/thaw cycling *	C1026	As reported	RESISTANT
 Resistance to thermal shock	C484	As reported	RESISTANT
 Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	COMPLY WITH ANSI A137.1
 Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	COMPLY WITH ANSI A137.1
 Wedging	C502	± 0.25% or ± 0.03 in	COMPLY WITH ANSI A137.1
 Chemical resistance	C650	As reported	UNAFFECTED
 Resistance to stain	C1378	As reported	UNAFFECTED
 Thickness	C499	Range: 0.04 in	COMPLY WITH ANSI A137.1
 Breaking strength	C648	250 lbf or greater	COMPLY WITH ANSI A137.1

* Average values referred to our production and related to the matt finish of the product.

- Be sure to use porcelain veneers belonging to the same caliber.

- Test results are available on request.

- The information provided can be subject to change. Please refer to [outdoor.landmarkceramics.com](https://www.outdoor.landmarkceramics.com) for the latest, most accurate and up-to-date information.

November 2023 - © Landmark Ceramics







LEARN MORE ABOUT









[outdoor.landmarkceramics.com](https://www.outdoor.landmarkceramics.com)